



- NOTES:
1. DRAWINGS FOR SPECIFICATION PURPOSES AND ARE FOR REFERENCE ONLY.
 2. ALL VERSIONS OF THE DRAWING ARE SUPERSEDED BY THIS RELEASE AND SUBJECT TO CHANGE WITHOUT NOTIFICATION.
 3. MATERIAL: 316L SST, SEMI F20.
 4. INTERNAL FINISHES: MACHINED AND ELECTROPOLISHED TO 5 Ra MAX.

| | | |
|---|-----------------------------------|---|
| EFFECTIVE DATE: 2/6/2017 | | INNOVATION WITH PRECISION 1003 INDUSTRIAL DRIVE SAUK RAPIDS, MN 56379 VOICE: 320-251-0390 FAX: 320-251-5810 |
| INTERPRET DRAWING PER: ASME Y14.5 - 2009 | | |
| THIRD ANGLE PROJECTION | | |
| PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TALON INNOVATIONS, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TALON INNOVATIONS, INC. IS PROHIBITED. | | DESCRIPTION: TMS 1.125" W-SEAL INSERT, I/O MANIFOLD LEFT |
| SIZE C | PART NUMBER: 03-10-0130 | |
| DO NOT SCALE DRAWING | | SCALE: 3:1 SHEET 1 OF 1 |